

Model Show: PF150-3AT

Specification

Description	15" TFT LCD Open Frame Monitor(touchscreen optional)		
Model	PF150-3AT(without touchscreen: PF150-3A)		
Screen Size	15"		
Touch Screen	4-Wire Resistive Touch(5-Wire for Optional)		
Touch Interface	USB (RS232 for Optional)		
Resolution	1024x768 pixels (max to1920×1440)		
Aspect Ratio	4:3		
Brightness	350cd/m ²		
Contrast Ratio	600:1		
Backlight	LED		
Response time	35ms		
Viewing Angle	70°/70°(L/R) 70°/65°(U/D)		
Interface(Optional)	PF150-3AHDT: HDMI,DVI,VGA,YPbPr,Video,Audio in,Audio out,USB for touch		
	PF150-3AHT: Audio out,Audio in,HDMI,VGA,AV1,AV2		
	PF150-3AT: VGA, S-video,Video,Audio R/L in,Audio in,Audio out,USB for touch		
Input Voltage	DC9-18V		
Power Consumption	≤26W		
working Temperature	-10℃～50℃		
storage Temperature	-20℃～65℃		
Unit Size	346.6 L×279.6H×45D (mm)		
Unit Weight	3700g		
OS Support for touch	Accessory	Packing	
Window 7,Vista, XP	Home AC Adapter	Box size	41x13.1x41.5CM
Window NT4	Remote Controller	Per box G.W.	8kg
Window 9X/ME	Touch Drive Disc(for touch)	Per Carton	2pcs
WIN CE	Touch Pen(for touch)	Carton Size	47x43.2x33.2CM
MAC	VGA Cable	N.W.	15kgs/carton
MS-DOS	USB cable(for touch)	G.W.	16kgs/carton
Linux			